SAFETY DATA SHEET

1. Identification

n laonanou lon				
Product identifier	KD100D KNOCK DOWN CRAWLING INSECT KILLER III			
Other means of identification				
Product code	KD100D			
Recommended use	PESTICIDE			
Recommended restrictions	None known.			
Manufacturer/Importer/Supplier/Distributor information				
Manufacturer				
Company name Address	KUUS INC. 450 TAPSCOTT ROAD SCARBOROUGH, ON M1B 1Y4 Canada	4 440 000 77		
Telephone E-mail	General Assistance Not available.	1-416-298-77	/24	
Emergency phone number	Emergency - US Emergency - Outside US	1-866-836-88 1-952-852-46		
Supplier	Not available.			
2. Hazard(s) identification				
Physical hazards	Flammable aerosols		Category 1	
Health hazards	Sensitization, skin		Category 1	
	Aspiration hazard		Category 1	
		>		
Signal word	Danger			
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.			
Precautionary statement				
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.			
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.			
Storage	Store locked up. Protect from s	sunlight. Do not	expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container i	in accordance v	with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic envir hazard	onment, acute	Category 1	
	Hazardous to the aquatic envir long-term hazard	onment,	Category 1	
Other hazards	None known.			
Supplemental information	None.			

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	15 - 40
Naphtha (Petroleum), Hydrotreated Heavy	1	64742-48-9	5 - 10
Propane		74-98-6	3 - 7
Distillates (petroleum), Hydrotreated Light		64742-47-8	1 - 5
White Mineral Oil		8042-47-5	1 - 5
Permethrin		52645-53-1	0.1 - 1
Other components below reportabl	e levels		40 - 70

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	
	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with

water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Fire fighting equipment/instructions

Specific methods

General fire hazards

Extremely flammable aerosol.

breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol.
	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Canada. Alberta OELs (Oc	cupational Health & Safety Code,	Schedule 1, Table 2)	
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1000 ppm	
Canada. British Columbia Safety Regulation 296/97, a		imits for Chemical Substances, C	Occupational Health and
Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Canada. Manitoba OELs (F	Reg. 217/2006, The Workplace Sat	fety And Health Act)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Canada. Ontario OELs. (Co	ontrol of Exposure to Biological o	or Chemical Agents)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	TWA	800 ppm	
Canada. Quebec OELs. (M Components	inistry of Labor - Regulation Res _l Type	pecting the Quality of the Work E Value	nvironment)
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	
		loss ppm	
logical limit values	No biological exposure limits no	ted for the ingredient(s)	
logical limit values posure guidelines	No biological exposure limits no	ted for the ingredient(s).	
•		ted for the ingredient(s).	
oosure guidelines Canada - British Columbia	OELs: Skin designation	ted for the ingredient(s). Can be absorbed through the skin.	
oosure guidelines Canada - British Columbia Distillates (petroleum), ł	OELs: Skin designation Hydrotreated Light (CAS Good general ventilation (typica should be matched to conditions or other engineering controls to		ures, local exhaust ventilation ommended exposure limits. If
Dosure guidelines Canada - British Columbia Distillates (petroleum), H 64742-47-8) propriate engineering htrols	OELs: Skin designation Hydrotreated Light (CAS Good general ventilation (typica should be matched to conditions or other engineering controls to	Can be absorbed through the skin. Ily 10 air changes per hour) should s. If applicable, use process enclosu maintain airborne levels below reco established, maintain airborne levels	ures, local exhaust ventilation ommended exposure limits. If
Dosure guidelines Canada - British Columbia Distillates (petroleum), H 64742-47-8) propriate engineering htrols	OELs: Skin designation Hydrotreated Light (CAS Good general ventilation (typical should be matched to conditions or other engineering controls to exposure limits have not been e	Can be absorbed through the skin. Ily 10 air changes per hour) should s. If applicable, use process enclosu maintain airborne levels below reco established, maintain airborne levels	ures, local exhaust ventilation ommended exposure limits. If to an acceptable level.
oosure guidelines Canada - British Columbia Distillates (petroleum), H 64742-47-8) propriate engineering ntrols	OELs: Skin designation Hydrotreated Light (CAS Good general ventilation (typical should be matched to conditions or other engineering controls to exposure limits have not been e s, such as personal protective eq Face shield is recommended. W	Can be absorbed through the skin. Ily 10 air changes per hour) should s. If applicable, use process enclose maintain airborne levels below reco established, maintain airborne levels uipment	ures, local exhaust ventilation ommended exposure limits. If to an acceptable level. s (or goggles).

Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Oday threehold	Not available.
Odor threshold	Not available.
pH Malting paint/freezing paint	Not available.
Melting point/freezing point	
Initial boiling point and boiling range	149.18 °F (65.1 °C) estimated
Flash point	-99.4 °F (-73.0 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	1.2 % estimated
Flammability limit - upper (%)	9.3 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	720.14 °F (382.3 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.844 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditic
Chemical stability	I ne product is stable and non-reactive under normal condition

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

information on likely routes of	exposure	
Inhalation	No adverse effects due to inhalation are expected.	
Skin contact	May cause an allergic skin reaction.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.	
Information on toxicological ef	fects	
Acute toxicity	May be fatal if swallowed and en	ters airways. May cause an allergic skin reaction.
Components	Species Test Results	
Distillates (petroleum), Hydrotrea	ted Light (CAS 64742-47-8)	
Acute		
Dermal LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Isobutane (CAS 75-28-5)		
Acute		

1237 mg/l, 120 Minutes

52 %, 120 Minutes

658 mg/l/4h

<u>Acute</u> In

Inhalation	
LC50	Mouse

Napl

	Rat	1355 mg/l
ohtha (Petroleum), Hydr	rotreated Heavy (CAS 64742-48-9)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours

		> 4.96 mg/l, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species		Test Results	
White Mineral Oil (CAS 8042-47-5	5)			
Acute				
Dermal LD50	Rabbit		> 2000 mg/kg, 24 Hours	
Inhalation LC50	Rat		2.18 mg/l, 4 Hours	
Oral				
LD50	Rat		> 5000 mg/kg	
			5000.0001 mg/kg	
* Estimates for product may I	be based on a	additional component data not shown.		
Skin corrosion/irritation	Prolonaed	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	-	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not a respi	iratory sensitizer.		
Skin sensitization	Mav cause	an allergic skin reaction.		
Germ cell mutagenicity	No data av	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	•	ncer cannot be excluded with prolonged ex	posure.	
IARC Monographs. Overall	Evaluation o	of Carcinogenicity		
Permethrin (CAS 52645	-53-1)	3 Not classifiable as t	to carcinogenicity to humans.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classifi	ied.		
Aspiration hazard	May be fatal if swallowed and enters airways.			
Chronic effects	Prolonged	exposure may cause chronic effects.		
12. Ecological information	n			
Ecotoxicity	Very toxic	to aquatic life with long lasting effects.		
Components		Species	Test Results	
Distillates (petroleum), Hydro	treated Light	(CAS 64742-47-8)		
Aquatic				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours	
Permethrin (CAS 52645-53-1)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	0.0006 - 0.0025 mg/l, 48 hours	
Fish	LC50	Apache trout (Oncorhynchus gilae apache)	0.0013 - 0.0022 mg/l, 96 hours	
White Mineral Oil (CAS 8042	-47-5)			
Aquatic	-			
Fish	LC50	Fish	10000.0001, 96 Hours	
* Estimates for product may I	be based on a	additional component data not shown.		
Persistence and degradability Bioaccumulative potential		available on the degradability of this produ	ict.	
Partition coefficient n-	octanol / wate			
Isobutane		2.76		

Permethrin Propane

Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	D
	${f r}$ Read safety instructions, SDS and emergency procedures before handling.
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es) Class	
Subsidiary risk	2.1
Label(s)	-
Packing group	2.1
Environmental hazards	Not applicable. Yes
ERG Code	10L
Special precautions for use	r Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	
Label(s)	None
Packing group Environmental hazards	Not applicable.
Marine pollutant	Voo
EmS	Yes F-D, S-U
	r Read safety instructions, SDS and emergency procedures before handling. Read safety
	instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG; TDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed. Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable. Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	03-29-2018
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names Hazard(s) identification: Hazard statement Hazard(s) identification: Response Hazard(s) identification: Storage Hazard(s) identification: GHS Symbols Composition / Information on Ingredients: Component Summary First-aid measures: Most important symptoms/effects, acute and delayed Handling and storage: Precautions for safe handling Handling and storage: Conditions for safe storage, including any incompatibilities Toxicological information: Acute toxicity Toxicological information: Aspiration hazard Toxicological information: Ingestion Toxicological information: Symptoms related to the physical, chemical and toxicological characteristics GHS: Classification