# SAFETY DATA SHEET

#### 1. Identification

Product identifier	KD241P KNOCK DOWN X-N	IAX FARM AND LIVESTOCK INSECT KILLER
Other means of identification		
Product code	KD241P	
Recommended use	Pesticide	
<b>Recommended restrictions</b>	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Manufacturer		
Company name	KUUS INC.	
Address	450 TAPSCOTT ROAD	
	SCARBOROUGH, ON M1B 1	Y4
	Canada	
Telephone	General Assistance	1-416-298-7724
E-mail	Not available.	
Emergency phone number	Canutec	1-888-226-8832
		1-613-996-6666

# 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Aspiration hazard	Category 1
Label elements		
	$\wedge \wedge$	
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May be fatal if	swallowed and enters airways.
Precautionary statement		
Prevention		pen flames and other ignition sources. No smoking. on source. Do not pierce or burn, even after use.
Response	IF SWALLOWED: Immediately call a POISON	CENTER/doctor. Do NOT induce vomiting.
Storage	Store locked up. Protect from sunlight. Do not	expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance	with local/regional/national/international regulations.
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
Other hazards	None known.	
Our set and a list for successful as	N 1	

Supplemental information None.

# 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), Heavy Alkylate		64741-65-7	40 - 70
Propane		74-98-6	15 - 40
Isobutane		75-28-5	7 - 13

Chemical name	Common name and synonyms	CAS number	%
Piperonyl Butoxide		51-03-6	3 - 7
Distillates (petroleum), Hydrotreated Light		64742-47-8	1 - 5
Pyrethrins		8003-34-7	0.1 - 1
Other components below reportable levels			0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
5 a , componente	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may

cause spark and become an ignition source. Store away from incompatible materials (see Section

#### 8. Exposure controls/personal protection

10 of the SDS).

Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Alberta OELs (Occ	upational Health & Safety Code, Sc	hedule 1, Table 2)	
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
	ELs. (Occupational Exposure Limit	ts for Chemical Substances, O	ccupational Health and
Safety Regulation 296/97, as	-	M. I	<b>F</b> orm
Components	Туре	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Manitoba OELs (Re	g. 217/2006, The Workplace Safety	And Health Act)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
Canada. Ontario OELs. (Cor	ntrol of Exposure to Biological or C	hemical Agents)	
Components	Туре	Value	
Isobutane (CAS 75-28-5)	TWA	800 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
-	istry of Labor - Regulation Respec	ting the Quality of the Work E	nvironment)
Components	Туре	Value	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3	
logical limit values	No biological exposure limits noted	for the ingredient(s).	
osure guidelines			
Canada - British Columbia (	DELs: Skin designation		
Distillates (petroleum), Hy 64742-47-8)	/drotreated Light (CAS Car	n be absorbed through the skin.	
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
	such as personal protective equip		

Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear suitable protective clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

-	-
Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.2 % estimated
Flammability limit - upper (%)	7.8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	718.6 °F (381.44 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion (NFPA 30B)	41.23 kJ/g estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.222 estimated
VOC (Weight %)	84.71 % estimated

## 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of e	exposure
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis.

#### Information on toxicological effects

· · · · · · · · · · · · · · · · · · ·	,	,	
Components	Species	Test Results	
Distillates (petroleum), Hydro	treated Light (CAS 64742-47-8)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
		> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	> 7.5 mg/l, 6 Hours	
		> 4.6 mg/l, 4 Hours	
Oral			
LD50	Rat	> 5000 mg/kg	
sobutane (CAS 75-28-5)			
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
Piperonyl Butoxide (CAS 51-	03-6)		
Acute			
Dermal			
LD50	-	> 2000 mg/kg	
Inhalation			
LC50	Rat	> 5.2 mg/l, 4 Hours	
Oral			
LD50	Rat	> 2000 mg/kg	
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	

Components	Species		Test Results
	658 mg/l/4h		
* Estimates for product may b	be based on additional o	component data not shown.	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitizatio	n		
Canada - British Columbia	OELs: Respiratory or	skin sensitiser	
Pyrethrins (CAS 8003-34	I-7) Capable of causing respiratory, dermal or conjunctival sensitization.		espiratory, dermal or conjunctival
<b>Respiratory sensitization</b>	Not a respiratory sen	sitizer.	
Skin sensitization	This product is not ex	xpected to cause skin sensitizati	on.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity			
ACGIH Carcinogens			
Pyrethrins (CAS 8003-34 Canada - Manitoba OELs: c		A4 Not classifiable as	s a human carcinogen.
PYRETHRUM (CAS 800		Not classifiable as a	human carcinogen.
IARC Monographs. Overall		genicity	
Piperonyl Butoxide (CAS			to carcinogenicity to humans.
Reproductive toxicity	This product is not ex	xpected to cause reproductive o	r developmental effects.
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity -	Not classified.		
repeated exposure			
repeated exposure Aspiration hazard	May be fatal if swallo	wed and enters airways.	
	-	wed and enters airways.	
Aspiration hazard	n	wed and enters airways. life with long lasting effects.	
Aspiration hazard	n	life with long lasting effects.	Test Results
Aspiration hazard <b>12. Ecological information</b> Ecotoxicity <u>Components</u> Distillates (petroleum), Hydro	n Very toxic to aquatic Spec	life with long lasting effects.	Test Results
Aspiration hazard 12. Ecological information Ecotoxicity Components	n Very toxic to aquatic Spec treated Light (CAS 647 LC50 Raint	life with long lasting effects. <b>ies</b> 42-47-8) bow trout,donaldson trout	<b>Test Results</b> 2.9 mg/l, 96 hours
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy	n Very toxic to aquatic Spec treated Light (CAS 647 LC50 Raint (Once	life with long lasting effects. <b>ies</b> 42-47-8) bow trout,donaldson trout orhynchus mykiss)	
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy Aquatic	n Very toxic to aquatic Spec treated Light (CAS 6474 LC50 Raint (Onco Alkylate (CAS 64741-68	life with long lasting effects. ies 42-47-8) bow trout,donaldson trout orhynchus mykiss) 5-7)	2.9 mg/l, 96 hours
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy Aquatic Algae	n Very toxic to aquatic Spec treated Light (CAS 6474 LC50 Raint (Onco Alkylate (CAS 64741-68 IC50 Algae	life with long lasting effects. ies 42-47-8) bow trout,donaldson trout orhynchus mykiss) 5-7)	
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy Aquatic	n Very toxic to aquatic Spec treated Light (CAS 6474 LC50 Raint (Onco Alkylate (CAS 64741-68 IC50 Algae	life with long lasting effects. ies 42-47-8) bow trout,donaldson trout orhynchus mykiss) 5-7)	2.9 mg/l, 96 hours
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy Aquatic Algae Piperonyl Butoxide (CAS 51-	n Very toxic to aquatic Spec treated Light (CAS 6474 LC50 Raint (Onco Alkylate (CAS 64741-65 IC50 Algae 03-6) LC50 Raint	life with long lasting effects. ies 42-47-8) bow trout,donaldson trout orhynchus mykiss) 5-7)	2.9 mg/l, 96 hours
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy Aquatic Algae Piperonyl Butoxide (CAS 51-4 Aquatic	n Very toxic to aquatic Spec treated Light (CAS 6474 LC50 Raint (Onco Alkylate (CAS 64741-65 IC50 Algae 03-6) LC50 Raint	life with long lasting effects. ies 42-47-8) bow trout,donaldson trout borhynchus mykiss) 5-7) bow trout,donaldson trout	2.9 mg/l, 96 hours 30000 mg/L, 72 Hours
Aspiration hazard 12. Ecological information Ecotoxicity Components Distillates (petroleum), Hydro Aquatic Fish Naphtha (petroleum), Heavy Aquatic Algae Piperonyl Butoxide (CAS 51-4 Aquatic Fish Pyrethrins (CAS 8003-34-7)	n Very toxic to aquatic Spec treated Light (CAS 6474 LC50 Raint (Onco Alkylate (CAS 64741-65 IC50 Algae 03-6) LC50 Raint (Onco	life with long lasting effects. ies 42-47-8) bow trout,donaldson trout borhynchus mykiss) 5-7) bow trout,donaldson trout	2.9 mg/l, 96 hours 30000 mg/L, 72 Hours

\* Estimates for product may be based on additional component data not shown.

 Persistence and degradability
 No data is available on the degradability of this product.

 Bioaccumulative potential
 Partition coefficient n-octanol / water (log Kow)

Isobutane	-	-	-	2.76
Piperonyl Butoxide				4.75

Partition coefficient	t n-octanol / water (log Kow)	
Propane	2.36	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal considera	tions	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used	

container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Dispose in accordance with all applicable regulations.
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

# 14. Transport information

TDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
Special precautions for user	r Read safety instructions, SDS and emergency procedures before handling.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG; TDG



**General information** 

IMDG Regulated Marine Pollutant.

#### 15. Regulatory information

#### **Canadian regulations**

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

**Precursor Control Regulations** 

Not regulated.

#### International regulations

Stockholm Convention Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable. Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

instructions, SDS and emergency procedures before handling. Not applicable.

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yet \*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other Information

Issue date	06-06-2019
Revision date	06-06-2019
Version #	02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.