SAFETY DATA SHEET

1. Identification

Product identifier MS0016 MOSQUITO SHIELD WILDERNESS FORMULA INSECT REPELLENT

Other means of identification

Product code MS0016

Recommended use Insect repellent
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name KUUS INC.

Address 450 TAPSCOTT ROAD

SCARBOROUGH, ON M1B 1Y4

Canada

Telephone General Assistance 1-416-298-7724

E-mail Not available.

Emergency phone number Canutec 1-888-226-8832

1-613-996-6666

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsAcute toxicity, oralCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye

irritation.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Do not eat, drink or smoke when using

this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth. IF ON SKIN

(or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of

fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethyl Alcohol		64-17-5	60 - 100
N,n-diethyl-m-toluamide (DEET)		134-62-3	15 - 40
Other components below reportal	ole levels		3 - 7

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

LIC ACCILL Three healed Limit Values

Occupational exposure limits

Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm
Canada. Alberta OELs (Occupation	nal Health & Safety Code, Sc	hedule 1, Table 2)
Components	Туре	Value
Ethyl Alcohol (CAS 64-17-5)	TWA	1880 mg/m3
		1000 ppm
Safety Regulation 296/97, as amen	ded)	s for Chemical Substances, Occupational Health and
Components	Туре	Value
Components Ethyl Alcohol (CAS 64-17-5)	Type STEL	Value 1000 ppm
<u> </u>	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/	STEL	1000 ppm
Ethyl Alcohol (CAS 64-17-5)	STEL 2006, The Workplace Safety	1000 ppm And Health Act)
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/ Components	STEL 2006, The Workplace Safety Type STEL	1000 ppm And Health Act) Value 1000 ppm
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/2006) Components Ethyl Alcohol (CAS 64-17-5) Canada. Ontario OELs. (Control of	STEL 2006, The Workplace Safety Type STEL	1000 ppm And Health Act) Value 1000 ppm
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/2 Components Ethyl Alcohol (CAS 64-17-5)	STEL 2006, The Workplace Safety Type STEL Exposure to Biological or C	1000 ppm And Health Act) Value 1000 ppm hemical Agents)
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/2 Components Ethyl Alcohol (CAS 64-17-5) Canada. Ontario OELs. (Control of Components Ethyl Alcohol (CAS 64-17-5)	STEL 2006, The Workplace Safety Type STEL Exposure to Biological or C Type STEL	1000 ppm And Health Act) Value 1000 ppm hemical Agents) Value
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/2006) Components Ethyl Alcohol (CAS 64-17-5) Canada. Ontario OELs. (Control of Components Ethyl Alcohol (CAS 64-17-5) Canada. Quebec OELs. (Ministry of	STEL 2006, The Workplace Safety Type STEL Exposure to Biological or C Type STEL	1000 ppm And Health Act) Value 1000 ppm hemical Agents) Value 1000 ppm
Ethyl Alcohol (CAS 64-17-5) Canada. Manitoba OELs (Reg. 217/2 Components Ethyl Alcohol (CAS 64-17-5) Canada. Ontario OELs. (Control of Components Ethyl Alcohol (CAS 64-17-5)	STEL 2006, The Workplace Safety Type STEL Exposure to Biological or C Type STEL STEL f Labor - Regulation Respec	1000 ppm And Health Act) Value 1000 ppm hemical Agents) Value 1000 ppm ting the Quality of the Work Environment)

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point 130.6 °F (54.8 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

3.3 % estimated

(%)

Flammability limit - upper

(%)

19 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 664.12 °F (351.18 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive.

Flammability class Combustible II estimated

Heat of combustion (NFPA

30B)

24.7 kJ/g estimated

Oxidizing properties Not oxidizing. Specific gravity

0.305 estimated VOC (Weight %) 65.28 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. Causes serious eye irritation. Eye contact

Harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Coughing. Skin irritation. May cause redness and pain.

Information on toxicological effects

Harmful if swallowed. **Acute toxicity**

Components	Species	Test Results
Ethyl Alcohol (CAS 64-17-5)		
<u>Acute</u>		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours

43.68 mg/l, 6 Hours Mouse > 60000 ppm

79.43 mg/l, 134 Minutes Rat > 115.9 mg/l, 4 Hours

51.3 mg/l, 6 Hours

Oral

LD50 Monkey 6000 mg/kg

> 10500 ml/kg Mouse Pig > 5000 mg/kg 10470 mg/kg Rat 7800 ml/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

^{*} Estimates for product may be based on additional component data not shown.

Germ cell mutagenicity No data available

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Canada - Manitoba OELs: carcinogenicity

ETHANOL (CAS 64-17-5) Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

ComponentsSpeciesTest ResultsEthyl Alcohol (CAS 64-17-5)AquaticCrustaceaEC50Water flea (Daphnia magna)7700 - 11200 mg/l, 48 hoursFishLC50Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours

N,n-diethyl-m-toluamide (DEET) (CAS 134-62-3)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 106 - 114 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethyl Alcohol -0.31 N,n-diethyl-m-toluamide (DEET) 2.02

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

 $local/regional/national/international\ regulations.$

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

UN number UN1993

UN proper shipping name F

Flammable liquid, n.o.s. (C9 - C11 Isoalkanes)

Transport hazard class(es)

Class 3 Subsidiary risk -

^{*} Estimates for product may be based on additional component data not shown.

Ш Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

3

IMDG

UN number UN1993

UN proper shipping name Transport hazard class(es) FLAMMABLE LIQUID, N.O.S. (C9 - C11 Isoalkanes)

Class

Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant No. F-E, S-E **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other Information

Issue date 06-07-2019

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.