# **SAFETY DATA SHEET**

1. Identification

Product identifier KD111P PROFESSIONAL KNOCK DOWN BEDBUG, ANT, COCKROACH, FLEA & TICK

Other means of identification INSECT KIL

Product code KD111P
Recommended use Pesticide
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name KUUS INC.

Address 450 TAPSCOTT ROAD

SCARBOROUGH, ON M1B 1Y4

Canada

**Telephone** General Assistance 1-416-298-7724

**E-mail** Not available.

Emergency phone number Canutec 1-888-226-8832

1-613-996-6666

2. Hazard(s) identification

**Physical hazards** 

Health hazards Flammable aerosols Category 1

Label elements Not classified.



Signal word Danger

Hazard statement Extremely flammable aerosol.

**Precautionary statement** 

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response Not available.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

Other hazards None known.

Supplemental information None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	15 - 40
Distillates (petroleum), Hydrotreated Light		64742-47-8	7 - 13
Propane		74-98-6	3 - 7

Chemical name	Common name and synonyms	CAS number	%
Piperonyl Butoxide		51-03-6	1 - 5
Pyrethrins		8003-34-7	0.1 - 1
Other components below re	eportable levels		40 - 70

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eve contact** Rinse with water. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control center.

Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

Treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

During fire, gases hazardous to health may be formed.

Direct contact with eyes may cause temporary irritation.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

LIS	<b>ACGIH</b>	Threshold	d I imit	Values
UO.	ACGIR	THESHOR	u Liiiiii	values

Components	Туре	Value
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
Canada. Alberta OELs (Occupation	nal Health & Safety Code, Scl	nedule 1, Table 2)
Components	Туре	Value
Propane (CAS 74-98-6)	TWA	1000 ppm
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
Safety Regulation 296/97, as amen		s for Chemical Substances, Occupational Health
Components	Туре	Value Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3 Non-aerosol.
Pyrethrins (CAS 8003-34-7)	TWA	5 mg/m3
Pyrethrins (CAS 8003-34-7)  Canada. Manitoba OELs (Reg. 217)		· ·
•		· ·
Canada. Manitoba OELs (Reg. 217/	/2006, The Workplace Safety	And Health Act)
Canada. Manitoba OELs (Reg. 217/ Components	/2006, The Workplace Safety Type	And Health Act) Value
Canada. Manitoba OELs (Reg. 217/ Components Isobutane (CAS 75-28-5)	/2006, The Workplace Safety Type  STEL TWA	And Health Act) Value  1000 ppm 5 mg/m3
Canada. Manitoba OELs (Reg. 217/ Components Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)	/2006, The Workplace Safety Type  STEL TWA	And Health Act) Value  1000 ppm 5 mg/m3
Canada. Manitoba OELs (Reg. 217/ Components  Isobutane (CAS 75-28-5)  Pyrethrins (CAS 8003-34-7)  Canada. Ontario OELs. (Control of	72006, The Workplace Safety Type  STEL TWA Exposure to Biological or Cl	And Health Act) Value  1000 ppm 5 mg/m3 hemical Agents)
Canada. Manitoba OELs (Reg. 217/ Components  Isobutane (CAS 75-28-5)  Pyrethrins (CAS 8003-34-7)  Canada. Ontario OELs. (Control of Components	/2006, The Workplace Safety Type STEL TWA Exposure to Biological or Cl	And Health Act) Value  1000 ppm 5 mg/m3 nemical Agents) Value
Canada. Manitoba OELs (Reg. 217) Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)  Canada. Ontario OELs. (Control of Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)	/2006, The Workplace Safety Type  STEL TWA Exposure to Biological or Cl Type  TWA TWA	And Health Act) Value  1000 ppm 5 mg/m3 nemical Agents) Value  800 ppm
Canada. Manitoba OELs (Reg. 217) Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)  Canada. Ontario OELs. (Control of Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)	/2006, The Workplace Safety Type  STEL TWA Exposure to Biological or Cl Type  TWA TWA	And Health Act) Value  1000 ppm 5 mg/m3 hemical Agents) Value  800 ppm 5 mg/m3
Canada. Manitoba OELs (Reg. 217/Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)  Canada. Ontario OELs. (Control of Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)  Canada. Quebec OELs. (Ministry o	/2006, The Workplace Safety Type  STEL TWA Exposure to Biological or Cl Type  TWA TWA TWA	And Health Act) Value  1000 ppm 5 mg/m3 hemical Agents) Value  800 ppm 5 mg/m3 ting the Quality of the Work Environment)
Canada. Manitoba OELs (Reg. 217/Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)  Canada. Ontario OELs. (Control of Components  Isobutane (CAS 75-28-5) Pyrethrins (CAS 8003-34-7)  Canada. Quebec OELs. (Ministry of Components)	/2006, The Workplace Safety Type  STEL TWA Exposure to Biological or Cl Type  TWA TWA TWA f Labor - Regulation Respect	And Health Act) Value  1000 ppm 5 mg/m3 hemical Agents) Value  800 ppm 5 mg/m3 sing the Quality of the Work Environment) Value

# **Biological limit values**

No biological exposure limits noted for the ingredient(s).

#### **Exposure guidelines**

### Canada - British Columbia OELs: Skin designation

Distillates (petroleum), Hydrotreated Light (CAS Can be absorbed through the skin.

64742-47-8)

# Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

149.18 °F (65.1 °C) estimated

Flash point -99.4 °F (-73.0 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 % estimated

(%)

Flammability limit - upper

4.9 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 40.83 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 610.52 °F (321.4 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Explosive properties** Not explosive.

Flammability class Flammable IB estimated
Heat of combustion (NFPA 17.02 kJ/g estimated

30B)

Oxidizing properties Not oxidizing.

Specific gravity 0.838 estimated

VOC (Weight %) 0.59 % estimated

# 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Nitrates. Fluorine. Chlorine.Hazardous decompositionNo hazardous decomposition products are known.

products

# 11. Toxicological information

#### Information on likely routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

#### **Acute toxicity**

Components	Species	Test Results
Distillates (petroleum), Hydro	otreated Light (CAS 64742-47-8)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Piperonyl Butoxide (CAS 51-	03-6)	
<u>Acute</u>		
Dermal		
LD50	-	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5.2 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

 Components
 Species
 Test Results

 Rat
 1355 mg/l

658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Canada - British Columbia OELs: Respiratory or skin sensitiser

Pyrethrins (CAS 8003-34-7) Capable of causing respiratory, dermal or conjunctival

sensitization.

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Pyrethrins (CAS 8003-34-7)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

PYRETHRUM (CAS 8003-34-7) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Piperonyl Butoxide (CAS 51-03-6) 3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results		
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)					
Aquatic					
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours		
Piperonyl Butoxide	(CAS 51-03-6)				
Aquatic					
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	0.0027 - 0.0043 mg/l, 96 hours		

Pyrethrins (CAS 8003-34-7)

Aquatic

 Crustacea
 EC50
 Water flea (Daphnia)
 0.018 - 0.032 mg/l, 48 hours

 Fish
 LC50
 Brown trout (Salmo trutta)
 0.0165 - 0.0229 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Isobutane2.76Piperonyl Butoxide4.75Propane2.36

Mobility in soil No data available.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

#### 14. Transport information

**TDG** 

UN number UN1950

UN proper shipping name Transport hazard class(es) AEROSOLS, flammable

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Environmental hazards Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This product meets the exemption requirements and may be shipped as a limited quantity.

**IATA** 

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant Yes
EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

#### IATA; IMDG; TDG



# Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

### **Canadian regulations**

**Controlled Drugs and Substances Act** 

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

**Greenhouse Gases** 

Not listed.

**Precursor Control Regulations** 

Not regulated.

# International regulations

#### **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

# **Kyoto protocol**

Not applicable.

#### **Montreal Protocol**

Not applicable.

# **Basel Convention**

Not applicable.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

Country(s) or region Inventory name On inventory (yes/no)\*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other Information

**Issue date** 06-06-2019

Version # 02

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names